

1.2-1.4GHz/1000Watt/Module

Model: KNP1300M60A

Model KNP1300M63A is an L-band high power pulsed amplifier operating in the 1.2 to 1.4GHz frequency range and offering pulsed width up to 50 μ S with duty cycle up to 20%. The amplifier provides in excess of 1000Watts peak output power into a 50 Ohm load. The employment of (LDMOS) and chip-and-wire technology in manufacturing ensures this module state-of-the-art power performance with excellent power-to-volume ratio. It is ideal for high power pulse applications or Radar system.

FEATURES:

- Small Size and light weight;
- Power added efficiency > 15%;
- Digital interface option;
- pulse width/duty cycle protection;
- Over voltage, and over current protection.

ELECTRICAL SPECIFICATIONS @ +50.0VDC, 25°C, 50 μ S, 10%, 50 Ω System

Parameter	Symbol	Min	Typ.	Max	Units
Operating Frequency	BW	1.2		1.4	GHz
RF Output Power	PPK	800	1000		Watt
Duty Cycle	Duty Cycle			20	%
Pulse Width	PWIDTH	2		100	μ S
Harmonics @ Pout = 800W	H		-20		dBc
Spurious Signals	Spur		-55		dBc
RF Input Power @ Pout = 1000W	PIN		0		dBm
Input Return Loss	S11		-10		dB
Switching Speed	TON/OFF		2		μ S
Power droop	Droop		1		dB
In/Output Impedance	Impedance		50		Ω
Operating Voltage	VDC	48	50	52	Volt
Peak Current Consumption @ Pout =1000W	IDD			30	Amp
Average Current Consumption @ Pout = 1000W	IDD		16		Amp

MECHANICAL SPECIFICATIONS

Parameter	Value	Units	Notes
Dimensions	300x 250 x30 [11.81x9.84x1.18]	mm [inch]	Max
Weight	5 [11]	kg [lb]	Max
RF Connectors Input	Type-SMA, Female		
RF Connectors Output	Type-N, Female		
DC Interface Connector	Hybrid, D-Sub 7-Pin, Male		
Cooling	External Heatsink Required (Optional supplying)		

ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-10		60	°C	
Non-operating Temperature	-20		65	°C	Storage
Relative Humidity (non-condensing)			95	%	

ABSOLUTE MAXIMUM RATING

Input RF drive level without damage	+5 dBm (Max)
Load VSWR @ POUT =500W	5:1 @ all load phase & amplitude for duration of 1 minute; 3:1 @ all load phase & amplitude continuous
Over Temperature	85°C @ heatsink [restored @ 60°C]

Focus on Your Application

Chengdu KeyLink Microwave Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761

>> Fax: +86(28)87883266

>> Email: sales@keylinkmw.com

>> www.keylinkmw.com

Specifications subject to change without notice


1.2-1.4GHz/1000Watt/Module

Model: KNP1300M60A

DC INTERFACE CONNECTOR

Pin #	Description	Specifications
A1	GND	Ground
A2	VDD	50VDC
1	UNIT RESET	Amplifier Reset: TTL Logic High (2.8-5.5V)
2	CURRENT SENSE	Analog voltage relative to IDD @ 100mV per Ampere
3	TEMP SENSE	Analog voltage relative to Module's Temperature @ 10 mV/°C
4	RF ON/OFF	RF On: TTL Logic High (2.8-5.5V)
5	NC	Not connect

OUTLINE DRAWING (All dimensions in mm [inch])



Focus on Your Application

Chengdu KeyLink Microwave Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761

>> Fax: +86(28)87883266

>> Email: sales@keylinkmw.com

>> www.keylinkmw.com


Specifications subject to change without notice

1.2-1.4GHz/1000Watt/Module


Model: KNP1300M60A

TYPICAL PERFORMANCE PLOTS (For reference only)

Graph 1: Output Power (Low temp. $-10\pm 3^{\circ}\text{C}$) (Duty Cycle 10%.Pulse Width 50 μs .PRI 500 μs)



Graph 2: Output Power (High temp. $+60\pm 3^{\circ}\text{C}$) (Duty Cycle 10%.Pulse Width 50 μs .PRI 500 μs)



Focus on Your Application

Chengdu KeyLink Microwave Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761

>> Fax: +86(28)87883266

>> Email: sales@keylinkmw.com


>> www.keylinkmw.com

Specifications subject to change without notice


1.2-1.4GHz/1000Watt/Module

Model: KNP1300M60A

Graph 3: Output Power (Normal temp. +25±3°C) (Duty Cycle 10%.Pulse Width 50µS.PRI 500µS)



Input Return Loss:



Note: Adequate heatsink required.

Focus on Your Application

Chengdu KeyLink Microwave Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761

>> Fax: +86(28)87883266

>> Email: sales@keylinkmw.com

>> www.keylinkmw.com

Specifications subject to change without notice